



ITEM	Hoshizaki Undercounter Refrigerator
MODEL	RT-126MA-SSG
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.50kVA (2.27A)
AMPERAGE	Rated 2.0A
ELECTRIC CONSUMPTION	Motor 238W(Power Factor*%) Heater 78W Refrigeration 295W Defrost 78W
HEAT REJECTION	*W
POWER CORD	2.0m (UK Plug with Earth Wire)
EFFECTIVE CAPACITY	231L
OUTSIDE DIMENSIONS	1200mm (W) x 600mm (D) x 850(-880) mm (H)
INSIDE DIMENSIONS	840mm (W) x 436mm (D) x 599mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom) Double Layer Glass with Heat Reflection Film(Glass Door)
INTERIOR	Stainless Steel
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Off Cycle
COMPRESSOR	Hermetic 280W (cooling capacity)
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R134a
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -2 to 12°C
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
LEG	Plastic Adjustable 150 to 180mm
SHELF	4pcs.
WEIGHT	Net: 82kg (Gross: Approx. 87kg)
PACKAGE	Carton 1265mm (W) x 680mm (D) x 790mm (H)
ACCESSORIES	Drain Hose x 1, Drain Pan x 1
OPERATING CONDITIONS	Ambient Temperature: 5-38°C Voltage Range: Rated Voltage \pm 6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The amperage and electric consumption are based on measurements at ambient temperature of 32°C and power supply of 220V 50Hz.
3. The cabinet temperature range of -2 to 12°C is guaranteed at ambient temperature of 25°C.
4. Depending on the installation environment, the glass door and the front frame of the body may dew and drop.
5. Product code: T236-C186 (HS)
6. During the operation of the machine, dew will form on the surface of the glass door.

*CUSTOMIZED
SLIDE GLASS DOOR
LED LAMP

HOSHIZAKI UNDERCOUNTER REFRIGERATOR RT-126MA-SSG

APPROVED KAWAKAMI	CHECKED WANG	DESIGNED LIANG	DRAWN KAWAKAMI	SCALE 1/20	TRIGONOMETRY
NAGASE	LIU	2019.8.12	DATE	2019.4.5	DRAWING NO. D24859
APPROVED	DESIGNED	SYMBOL	DATE		SYMBOL