



ITEM	HOSHIZAKI FLAKE ICE MAKER
△3 MODEL	FM-480AWKE(-SB)
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 2.7kVA (11.7A)
AMPERAGE	6.9A Starting: 43A
ELECTRIC CONSUMPTION	1385W (Power Factor: 87%)
ICE PRODUCTION PER 24h	Approx.420kg (Ambient Temp. 10°C, Water Temp. 10°C) Approx.380kg (Ambient Temp. 21°C, Water Temp. 15°C) Approx.340kg (Ambient Temp. 32°C, Water Temp. 21°C)
POTABLE WATER CONSUMPTION PER 24h	Approx. 0.42m ³ (AT. 10°C, WT. 10°C) Approx. 0.38m ³ (AT. 21°C, WT. 15°C) Approx. 0.34m ³ (AT. 32°C, WT. 21°C)
△3 CONDENSER WATER CONSUMPTION PER 24h	Approx. 1.207m ³ (AT. 10°C, WT. 10°C) Approx. 1.622m ³ (AT. 21°C, WT. 15°C) Approx. 2.410m ³ (AT. 32°C, WT. 21°C)
SHAPE OF ICE	Flake
MAX STORAGE CAPACITY	Not Applicable
OUTSIDE DIMENSIONS	560(W) x 700(D) x 780mm(H)
CABINET	Stainless Steel, Galvanized Steel (Rear)
ICE MAKING SYSTEM	Thin ice forming inside Cylinder (Flake Ice)
WATER SUPPLY SYSTEM	Direct Connection to Water Main, Inlet: G3/4, Cond.Inlet: Rc1/2 (Rear)
DRAIN SYSTEM	Outlet: R3/4, Cond.Outlet Rc3/8 (Rear)
COMPRESSOR	Hermetic
CONDENSER	Tube in Tube Type, Water-cooled
EVAPORATOR	Tube coiled around Cylinder (Solder Plated)
△3 REFRIGERANT	R404A/370g
BIN CONTROL	Actuator and Reed Switch (Time delay controlled)
ICE MAKING WATER CONTROL	Float Switch and Solenoid Valve
ELECTRIC CIRCUIT PROTECTION	Circuit Breaker, Earth Wire
REFRIGERANT CIRCUIT PROTECTION	Compressor Internal Thermostat (Auto-reset), Pressure Switch (Auto-reset)
MECHANISM PROTECTION	Micro Switch (Manual-reset)
△3 ICE MAKER PROTECTION	Shutdown by Microprocessor (Manual-reset)
WEIGHT	Net: 95kg(Gross: 102kg)
PACKAGE	Carton 665(W) x 820(D) x 950mm(H)
ACCESSORIES	Mounting Bracket, Installation Kit
OPERATING CONDITIONS	Ambient Temp.: 5 - 40°C, Water Supply Temp.: 5-35°C Water Supply Pressure: 0.05-0.8MPa(0.5-8bar) Voltage Range: Rated Voltage±10%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the ice maker properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.
2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.

△3. Use a cooling tower for cooling water.

△3.4. Product Code: F082-C120

F082-C122(SB Type)

HOSHIZAKI FLAKE ICE MAKER FM-480AWKE(-SB) [Auger Type]

APPROVED YOSHIDA	CHECKED KUROYANAGI	DESIGNED TAKAGI	DRAWN WATANABE	SCALE 1/20	TRIGONOMETRY
NISHIO	NAKATA	2018.11.12	DATE 2012.05.28	DRAWING NO. D11569	SYMBOL △3
APPROVED	DESIGNED	SYMBOL	DATE		