EQ−4101
様式−26

HOSHIZAKI



VIEW A



HONG KONG PLUG











ITEM	Hoshizaki Undercounter Freezer
MODEL	FTE−98SC−S
POWER SUPPLY	1 Phase 220−240V~ 50Hz Capacity: 0.60kVA (2.60A)
AMPERAGE	Rated 1.9A Starting 7.0A
ELECTRIC CONSUMPTION	Motor 145W(Power Factor 34%) Heater 209W Refrigeration 164W Defrost 190W
HEAT REJECTION	530W
POWER CORD	2.0m (UK Plug with Earth Wire)
EFFECTIVE CAPACITY	199L
OUTSIDE DIMENSIONS	900mm (W) x 750mm (D) x 850 (−880)mm (H)
INSIDE DIMENSIONS	540mm (W) x 585mm (D) x 599mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear / Bottom), PP (Handle on Door)
INTERIOR	Stainless Steel, ABS Plastic
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic, Inverter
CONDENSER	Fin and Tube type, Air−cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R290 / 53g
TEMPERATURE CONTROL	Microprocessor controlled Adjustable from −25 to −7°C
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Circuit Breaker, Earth Wire
COMPRESSOR PROTECTION	Inverter Protector (Auto−reset)
LEG	Plastic Adjustable 150 to 180mm
SHELF	2pcs.
WEIGHT	Net:78kg (Gross: Approx. 91kg)
PACKAGE	Carton 965mm (W) x 830mm (D) x 845mm (H)
ACCESSORIES	−
OPERATING CONDITIONS	Ambient Temperature: 5−43°C Voltage Range: Rated Voltage±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided.
   Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 35°C and power supply of 230V 50Hz.
   The amperage and electric consumption are based on measurements at ambient temperature of 43°C and power supply of 230V 50Hz.
3. The cabinet temperature range of −25 to −7°C is guaranteed at ambient temperature of 30°C.
4. Product code: T412−C100

HOSHIZAKI UNDERCOUNTER FREEZER FTE−98SC−S

APPROVED	CHECKED	DESIGNED	DRAWN	SCALE	
LIANGK	ZHOU	ZHOU	LXF	1/20	TRIGONOMETRY
*	*	△	*	DATE	DRAWING NO.	SYMBOL
APPROVED	DESIGNED	SYMBOL	DATE	2025.10.28	D43926	△

000520
施行